

ABOVE-GROUND-POOL CLOSING

- ✚ Vacuum the pool if necessary
- ✚ Lower the water level of the pool 14 to 18 inches below the skimmer (center drain on FULL DRAIN and filter on WASTE)
- ✚ Once the pool has reached the desired level, pour the liquid winterizer around the pool
- ✚ Remove the skimmer door, the basket and the eye and ring of the water return... Don't forget the thermometer
- ✚ Remove the ladder or the step
- ✚ Remove the big drain plug, the gauge and the backwash bottle from the sand filter
- ✚ Place the handle on the WINTER position or in between 2 positions
- ✚ Insert winterizing container into the float ring, then pierce 2 of the 4 tips. Place unit into the pool
- ✚ Remove all connecting hoses and store motor in the house
- ✚ Insert the styrofoam kit in the skimmer

✚ **CLOSING OF YOUR BOTTOM DRAIN**

- ✚ Unscrew the large nut under the bottom drain valve
- ✚ Attach the hose on the top rail of the pool with rope (the top of your hose has to be at the same level as your pool)
- ✚ Pour the pool anti-freeze in the hose and insert a length of styrofoam
- ✚ Install a winter cover and/or a leaf net if necessary
- ✚ Keep the valve at 1/2 1/2